

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 1/14
(30527329/CDU_GEN_US/EN)

1. Substance/preparation and company identification

Company

BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

Classification of the product

Skin corrosion/irritation	2	
Serious eye damage/eye irritation	2A	
Skin sensitization	1	
Specific target organ toxicity - single exposure	3	Vapours may cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	2	Central nervous system
Specific target organ toxicity - repeated exposure	2	Kidney
Specific target organ toxicity - repeated exposure	2	Liver
Hazardous to the aquatic environment - acute	2	
Hazardous to the aquatic environment - chronic	2	
Flammable liquids	2	

Label elements

Pictogram:

Flame
Exclamation mark
Environment
Health hazard

Signal Word:

Danger

Hazard Statement:

H319

Causes serious eye irritation.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 2/14
(30527329/CDU_GEN_US/EN)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H225	Highly flammable liquid and vapour.
H373	May cause damage to organs through prolonged or repeated exposure.
H336	May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.
P260	Do not breathe dust or mist.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P243	Take precautionary measures against static discharge.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P271	Use only outdoors or in a well-ventilated area.
P264	Wash with plenty of water and soap thoroughly after handling.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements (Response):

P391	Collect spillage.
P314	Get medical advice/attention if you feel unwell.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P321	Specific treatment (see on this label).
P362 + P364	Take off contaminated clothing and wash it before reuse.
P363	Wash contaminated clothing before reuse.
P370 + P378	In case of fire: Use water spray for extinction.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 3/14
(30527329/CDU_GEN_US/EN)

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Precautionary Statements (Storage):

P405 Store locked up.
P403 + P235 Store in a well-ventilated place. Keep cool.
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

Hazards not otherwise classified

No applicable information available.

According to Regulation 1994 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

Emergency overview

FLAMMABLE LIQUID
HARMFUL IF INHALED
CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE
CAN CAUSE LIVER DAMAGE
CAN CAUSE KIDNEY DAMAGE
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION
SUSPECT CANCER HAZARD
MAY CAUSE PULMONARY EDEMA
INGESTION MAY CAUSE GASTRIC DISTURBANCES

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
	5.0 - 7.0 %	Styrenated acrylic modified polyester
67-64-1	20.0 - 25.0 %	acetone
110-12-3	1.0 - 3.0 %	methyl isoamyl ketone
123-86-4	3.0 - 5.0 %	n-butylacetate
280-57-9	0.1 - 0.2 %	1,4-Diazabicyclooctane
7727-43-7	3.0 - 5.0 %	barium sulphate
41556-26-7	1.0 - 3.0 %	hindered amine light stabilizer
1330-20-7	1.0 - 3.0 %	xylene
82919-37-7	0.3 - 1.0 %	light stabilizer
64742-95-6	1.0 - 3.0 %	solvent naphtha (petroleum), light arom., <0.1% benzen
14807-96-6	1.0 - 3.0 %	talc

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 4/14
(30527329/CDU_GEN_US/EN)

According to Regulation 1994 OSHA Hazard Communication Standard;
29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
67-64-1	20.0 - 25.0 %	acetone
98-56-6	15.0 - 20.0 %	parachlorobenzotrifluoride
123-86-4	3.0 - 5.0 %	n-butylacetate
7727-43-7	3.0 - 5.0 %	barium sulphate
14807-96-6	1.0 - 3.0 %	talc
1330-20-7	1.0 - 3.0 %	xylene
41556-26-7	1.0 - 3.0 %	hindered amine light stabilizer
110-12-3	1.0 - 3.0 %	methyl isoamyl ketone
763-69-9	1.0 - 3.0 %	ethyl 3-ethoxypropionate
100-41-4	0.3 - 1.0 %	ethylbenzene

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
Remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air.
If breathing difficulties develop, aid in breathing and seek immediate medical attention.

If on skin:

Immediately wash thoroughly with soap and water. Seek medical attention.

If in eyes:

Flush with copious amounts of water for at least 15 minutes.
Hold eyelids open to facilitate rinsing.
If irritation develops, seek medical attention.
Seek medical attention.

If swallowed:

Rinse mouth and then drink plenty of water.
Do not induce vomiting due to aspiration hazard.
Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.
Immediate medical attention is required.

Most important symptoms and effects, both acute and delayed

Symptoms:

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 5/14
(30527329/CDU_GEN_US/EN)

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

Dry extinguishing media

Carbon dioxide

Foam

Water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Vapors and/or decomposition products are irritants and/or toxic.

If product is heated above decomposition temperatures, acrid smoke and fumes will be released.

Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Vapors are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition. Flash fire may occur.

Remove product from areas of fire or otherwise cool sealed containers with water in order to avoid pressure build-up due to heat.

Do not flood burning material with water due to potential spreading of fire.

Contain contaminated water/firefighting water.

Run-off water from fire may cause pollution.

Notify proper authorities.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Extinguish sources of ignition nearby and downwind.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 6/14
(30527329/CDU_GEN_US/EN)

Wear suitable personal protective clothing and equipment.
Ensure adequate ventilation.
Avoid prolonged inhalation.
Avoid contact with skin and eyes.
Use antistatic tools.

Environmental precautions
Do not discharge into drains/surface waters/groundwater.
A spill of or in excess of the reportable quantity requires notification to state, local and national emergency authorities.

Methods and material for containment and cleaning up
Dike spillage.
Place into appropriately labeled waste containers.
Spills should be contained, solidified, and placed in suitable containers for disposal.

7. Handling and Storage

Precautions for safe handling
Ensure adequate ventilation.
Do not puncture, drop or slide containers.
Use static lines when mixing and transferring material.
Handle and open container with care.
Avoid contact with the skin, eyes and clothing.
WARNING: Empty containers may still contain hazardous residue.
Do not apply to hot surfaces.
Proper ventilation and respiratory protection is required when sanding, flame cutting, welding or brazing coated surfaces.

Protection against fire and explosion:
Use antistatic tools.
Exhaust fans should be explosion proof.
Provide adequate ventilation to remove solvent vapors from lower levels or work areas and to prevent solvent contact with ignition sources.
Sealed containers should be protected against heat as this results in pressure build-up.
Risk of explosion if heated under confinement.
Avoid all sources of ignition: heat, sparks, or open flame.

Conditions for safe storage, including any incompatibilities
Segregate from incompatible substances.
Segregate from oxidizing agents.
Segregate from strong bases.
Segregate from strong acids.

Further information on storage conditions:
Keep container tightly closed.
Protect from direct sunlight.
Protect from temperatures above 49C/ 120F.
Consult local fire marshal for storage requirements.

Storage stability:

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 7/14
(30527329/CDU_GEN_US/EN)

8. Exposure Controls and Personal Protection

Components with occupational exposure limits

acetone

ACGIH STEL 750 ppm; TWA 500 ppm

OSHA PEL 1000 ppm 2400 mg/m³

ethylbenzene

ACGIH STEL 125 ppm; TWA 100 ppm

OSHA PEL 100 ppm 435 mg/m³

methyl isoamyl ketone

ACGIH TWA 50 ppm

OSHA PEL 100 ppm 475 mg/m³

n-butylacetate

ACGIH STEL 200 ppm; TWA 150 ppm

OSHA PEL 150 ppm 710 mg/m³

xylene

ACGIH STEL 150 ppm; TWA 100 ppm

OSHA PEL 100 ppm 435 mg/m³

barium sulphate

ACGIH TWA 10 mg/m³

OSHA PEL 5 mg/m³ R; PEL 15 mg/m³ T

talc

ACGIH TWA 2 mg/m³

R Respirable fraction

T Total dust

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

General mechanical ventilation should comply with OSHA 1910.94.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Wear NIOSH-certified (or equivalent) organic vapor respirator.

Particulate filters should be added during spray operations.

Do not exceed the maximum use concentration for the respirator

facepiece/cartridge combination.

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Use appropriate chemically resistant gloves as determined by an

evaluation of glove performance characteristics and the hazards

and potential hazards identified, including but not limited to

butyl, natural and synthetic rubber, nitrile, or neoprene.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Wear face shield if splashing hazard exists.

Body protection:

Body protection must be chosen based on activity level and

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 8/14
(30527329/CDU_GEN_US/EN)

exposure.

General safety and hygiene measures:

Work place should be equipped with a shower and eye wash.

Contact lenses should not be worn.

Remove contaminated clothing.

Contaminated equipment or clothing should be cleaned after each use or disposed of.

Hands and/or face should be washed before breaks and at the end of the shift.

9. Physical and Chemical Properties

Form:	liquid
Odour:	solvent-like
Odour threshold:	No applicable information available.
Colour:	off-white
pH value:	No applicable information available.
Melting temperature:	No applicable information available.
Boiling range:	133 - 354 Â°F / 56.1 - 178.9 Â°C
Sublimation temperature:	No applicable information available.
Flash point:	< 9 Â°F (< 12.8- Â°C) (calculated)
Flammability:	No applicable information available.
Lower explosion limit:	not available
Upper explosion limit:	not available
Autoignition:	No applicable information available.
Vapour pressure:	not available
Density:	8.69 Lb/USg CALC
Relative density:	1.04
Vapour density:	heavier than air
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No applicable information available.
Viscosity, dynamic:	No applicable information available.
Solids content:	approx. 46 % / 39.8404 % (V)
Viscosity, kinematic:	> 20.60 mm ² /s
Solubility in water:	No applicable information available.
% volatiles:	approx. 12.8 % / 15.3 % (V)
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.

10. Stability and Reactivity

Reactivity

Reactivity:

No applicable information available.

Chemical stability

Chemical stability:

The product is chemically stable.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 9/14
(30527329/CDU_GEN_US/EN)

Possibility of hazardous reactions

Hazardous reactions:
No applicable information available.

Conditions to avoid

Conditions to avoid:
Avoid all sources of ignition: heat, sparks or open flames.
Avoid electrostatic discharge.

Incompatible materials

Substances to avoid:
strong bases
strong oxidizing agents
strong acids

Hazardous decomposition products

Decomposition products:
carbon monoxide
carbon dioxide

Thermal decomposition:
No applicable information available.

11. Toxicological Information

Primary routes of exposure
Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Primary routes of entry:
Solvents are absorbed through the skin.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity:
The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: acetone
Assessment of acute toxicity:
High concentrations in the air may cause narcosis.

Information on: methyl isoamyl ketone
Assessment of acute toxicity:
Harmful by inhalation.

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 10/14
(30527329/CDU_GEN_US/EN)

Information on: 1,4-Diazabicyclooctane
Assessment of acute toxicity:
Of moderate toxicity after single ingestion.

Information on: solvent naphtha (petroleum), light arom., <0.1%
benzen
Assessment of acute toxicity:
Of pronounced toxicity after short-term skin contact.

Oral

Acute oral toxicity:
No applicable information available.

Inhalation

Acute inhalation toxicity:
No applicable information available.

Dermal

Acute dermal toxicity:
No applicable information available.

Assessment other acute effects

Assessment of STOT single:
Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects:
Eye contact causes irritation.
Skin contact causes irritation.

Information on: Styrenated acrylic modified polyester
Assessment of irritating effects:
Eye contact causes irritation.

Information on: acetone
Assessment of irritating effects:
Irritating to eyes.

Information on: 1,4-Diazabicyclooctane
Assessment of irritating effects:
Skin contact causes irritation.
May cause severe damage to the eyes.

Information on: xylene
Assessment of irritating effects:
Eye contact causes irritation.
Skin contact causes irritation.

Information on: solvent naphtha (petroleum), light arom., <0.1%

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 11/14
(30527329/CDU_GEN_US/EN)

benzen

Assessment of irritating effects:
Skin contact causes irritation.

Sensitization

Assessment of sensitization:
Sensitization after skin contact possible.

Information on: hindered amine light stabilizer

Assessment of sensitization:
Sensitization after skin contact possible.

Aspiration hazard

No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity:
Repeated exposure may affect certain organs.

Information on: acetone

Assessment of repeated dose toxicity:
The substance may cause damage to the testes after repeated ingestion of high doses, as shown in animal studies.
The substance may cause damage to the hematological system after repeated ingestion of high doses.
The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies.

Information on: methyl isoamyl ketone

Assessment of repeated dose toxicity:
May affect the liver and kidneys as indicated in animal studies.

Genetic toxicity

Assessment of mutagenicity:
No applicable information available.

Carcinogenicity

Assessment of carcinogenicity:
No applicable information available.

Reproductive toxicity

Assessment of reproduction toxicity:
The product has not been tested. The statement has been derived from the properties of the individual components.

Development

Assessment of teratogenicity:

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 12/14
(30527329/CDU_GEN_US/EN)

No applicable information available.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

No applicable information available.

13. Disposal Considerations

Waste disposal of substance

Dispose of in accordance with national, state and local regulations.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA.

Do not discharge into drains/surface waters/groundwater.

Incinerate or dispose of in a RCRA licensed facility.

Do not incinerate closed containers.

Container disposal

WARNING: Empty containers may still contain hazardous residue.

Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Hazard class: 3
Packing group: II
ID-number: UN 1263
Proper shipping name: Paint

Sea transport

IMDG

Hazard class: 3
Packing group: II
ID-number: UN 1263
Proper shipping name: Paint

Air transport

IATA/ICAO

Hazard class: 3
Packing group: II
ID-number: UN 1263

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 13/14
(30527329/CDU_GEN_US/EN)

Proper shipping name: Paint

15. Regulatory Information

Federal Regulations

Registration status

TSCA, US released / listed

EPCRA 313

CAS number	Weight %	Chemical name
1330-20-7	1.9	xylene
100-41-4	0.4	ethylbenzene

State regulations

State RTK

CAS Number	Chemical name
67-64-1	acetone
98-56-6	parachlorobenzotrifluoride
123-86-4	n-butylacetate
7727-43-7	barium sulphate
14807-96-6	talc
1330-20-7	xylene
110-12-3	methyl isoamyl ketone
100-41-4	ethylbenzene

CA Prop. 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

NFPA Hazard codes

Health: 2 Fire: 3 Reactivity: 0 Special:

HMIS III rating

Health: 2 Flammability: 3 Physical hazard: 0

16. Other information

SDS prepared by: BASF NA Product Regulations

SDS prepared on 16.06.2016

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the

Safety data sheet

LA5999 Suprme DTM Mix Clr

Revision date : 2016/06/16
Version: 10.0

Page: 14/14
(30527329/CDU_GEN_US/EN)

safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.